


DATE	PROJECT	FIRM	TYPE
------	---------	------	------



Rounded, linear luminaire with direct lighting. For use in indoor applications where a round profile that provides continuous light is required. Suitable for suspended installation. Custom outputs and colors available.

FEATURES

- Available In Custom Lengths & Long Runs accurate up to 1/16" Accuracy
- Damp Location Rated
- CRI 90+ Standard
- 2700K, 3000K, 3500K, 4000K & 5000K Color Temperatures Available

APPLICATIONS Commercial Interiors, Retail, Hospitality, Museums, Reception Areas

CONSTRUCTION Extruded Aluminum Housing and Sheet Metal End Caps. Formed Steel gear Tray. **OPTICS** Extruded High Transmission Satin Acrylic Lens With No LED Imaging.


WARRANTY 5 Year Limited Warranty (Covers Standard Components) **FINISH** Standard Powder-Coated White. Custom RAL Colors Available

FIXTURE RATINGS & CERTIFICATIONS Union Made ETL Listed Made In The USA Damp Location Rated



ELECTRICAL Integral Driver With 0-10V 10% Dimming Standard. Several Driver Options Available. See Below For Lutron Dimming Information

EXTRUSION DIMENSIONS



LED SYSTEM INFORMATION

	Nominal System Watts	Nominal Delivered Lumens	Nominal Efficacy
Standard (LTG1)	7.25 W/ft	675 Lm/ft	90 Lm/W
Low (LTG2)	5 W/ft	450 Lm/ft	90 Lm/W
High (LTG3)	8.75 W/ft	750 Lm/ft	86 Lm/W

Based on a 3500K luminaire using one driver. Please consult factory for custom lumen outputs & wattage.


ORDERING

1 - FIXTURE ID KCRD3-LED	2 - LENGTH 2 - 2 ft 4 - 4 ft 8 - 8 ft x'-x" - Custom (specify length) **Patterns available consult factory	3 - COLOR TEMP 27 - 2700K/90 CRI 30 - 3000K/90 CRI 35 - 3500K/90 CRI 40 - 4000K/90 CRI 50 - 5000K/90 CRI	4 - LED SYSTEM LTG1 - Standard LTG2 - Low LTG3 - High C - Custom Output (ie-C550Lm/ft)	5 - VOLTAGE UNV - Universal (120/277V)	6 - DRIVER (Remote) DB - Standard 10% Dimming (0-10V) DB1% - 1% Dimming (0-10V) DB.01% - .01% Dimming (0-10V) L3DA - Lutron 3-wire 1% Dimming LDE1 - Lutron Digital EcoSystem LDE5 - 5 Series EcoSystem; 5% Dimming
------------------------------------	--	--	---	--	--

7 - FINISH W - White (Standard) BLK - Black CC - Custom Color (provide RAL#)	8 - MOUNTING AC - Aircraft Cable (50")	9 - OPTICS SD - Standard Diffuser	10 - CIRCUIT (Optional) EM 120V - Emergency Pack EM 277V - Emergency Pack
--	--	---	--

DATE	PROJECT	FIRM	TYPE
------	---------	------	------


KCRD3-LED 4FT LTG1 3500K
 DELIVERED LUMENS: 2,701 Lm
 TOTAL WATTS: 30W
 EFFICACY: 93 Lumens/Watt



ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LAMP	% FIXTURE
0.00 - 30.00	723.37	21.64	25.95
0.00 - 40.00	1172.74	35.09	42.07
0.00 - 60.00	2043.39	61.14	73.30
0.00 - 90.00	2701.37	80.82	96.90
90.00 - 120.00	0.00	0.00	0.00
90.00 - 150.00	0.00	0.00	0.00
90.00 - 180.00	0.00	0.00	0.00
0.00 - 180.00	2701.37	83.40	100.00


KCRD3-LED 4FT LTG2 3500K
 DELIVERED LUMENS: 3,694Lm
 TOTAL WATTS: 20W
 EFFICACY: 93 Lumens/Watt



ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LAMP	% FIXTURE
0.00 - 30.00	486.28	21.64	25.95
0.00 - 40.00	788.04	35.08	42.06
0.00 - 60.00	1373.27	61.13	73.29
0.00 - 90.00	1815.80	80.82	96.91
90.00 - 120.00	0.00	0.00	0.00
90.00 - 150.00	0.00	0.00	0.00
90.00 - 180.00	0.00	0.00	0.00
0.00 - 180.00	1873.77	83.40	100.00

KCRD3-LED 4FT LTG3 3500K
 DELIVERED LUMENS: 3,026Lm
 TOTAL WATTS: 35W
 EFFICACY: 86 Lumens/Watt



ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LAMP	% FIXTURE
0.00 - 30.00	810.49	21.64	25.94
0.00 - 40.00	1314.29	35.08	42.06
0.00 - 60.00	2290.27	61.14	73.30
0.00 - 90.00	3028.00	80.83	96.91
90.00 - 120.00	0.00	0.00	0.00
90.00 - 150.00	0.00	0.00	0.00
90.00 - 180.00	0.00	0.00	0.00
0.00 - 180.00	3124.60	83.41	100.00